



X76 AWNING WINDOWS

≥1.8
Profile
Thick

76mm
Frame
Depth

35.3mm
Thermal
Barrier



OVERVIEW

A top-hung outward-opening window providing ventilation even in light rain. The awning sash pivots from the top, directing airflow downward and keeping water out.

KEY FEATURES & BENEFITS

- Top-hung design allows ventilation during rain without water ingress
- Friction stays hold sash at any open position for controlled airflow
- Winding arm operator available for high or difficult-to-reach installations
- Combines effectively with fixed X76 panels to create mixed-function facades
- Suitable for residential and light commercial use

- **THERMALLY BROKEN FRAMES**
Superior insulation for year-round comfort
- **SLIMLINE SIGHT LINES**
Maximum glass, minimal frame intrusion
- **CUSTOM POWDER COAT**
30+ color finishes to match any façade
- **NFRC CERTIFIED**
Meets NFRC Certifications Criteria



TECHNICAL SPECIFICATIONS

Frame Depth	76 mm (3")
Glazing	Double glazed; up to 28 mm (1 1/8") unit
Thermal Performance	Thermally broken aluminum
Water Tightness	Class 9A (AS 2047)
Max Sash Size	Approx. 1800 mm (W) x 900 mm (H) (35 7/16" x 70 7/8")
Hardware	Friction stays; multi-point locking; winding arm operator optional
Finish	Powder coat; extensive color range

ALSO AVAILABLE IN: PUSH OUT CASEMENT, & SWING DOOR **X76 AWNING WINDOWS**